Portable Autoclave LX105POA

Email: info@labdex.com **website:** www.labdex.com

Description

Portable autoclave LX105POA is an advanced steam sterilizer and portable N class unit with a capacity of 18 L, a sterilizing temperature is 126 °C and a 0~60 min timer range for providing efficient sterilization function. It can effectively discard all living organisms because of high pressure and maintained temperature. It's facilitated with a leak proof chamber, overheating or pressure warning indicator, work indicator light, automatic sound indication system after every cycle, Electric heated top loading high-pressure steam sterilizing unit and dual scale pressure gauge indicator.

Specifications

Volume of Chamber	18 L (280 x 260 mm)
Working temperature	126 ℃
Heating mode	Electrically heated
Timer range	0 ~ 60 min
Working pressure	0.14 ~ 0.16 Mpa
Max safety pressure	0.165 Mpa
Heat average	≤ ± 1℃
Temp adjustment	105 ~ 126 ℃
Power	AC 220 V / 50 Hz / 2 KW
Overall Dimension	410 × 410 × 520 mm
Net Weight	16 Kg
Gross Weight	18 Kg

Features

- Sterilizing Temperature 126 °C
- Equipped with pressure and overheating warning indicator
- Self-inflating Leak proof chamber
- Inner and outer Chamber formation by stainless steel
- Electric heated
- Dual pressure gauge indicator
- Automatically shut off with a beep sound reminding after every cycle of sterilization

- Safe and reliable

Applications

- Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com